



Installation Instructions - JLT Cold Air Intake 2006-10 Jeep SRT8 #CAI-SRTJ-06; #CAI-SRTJ-06-P

Thank you for purchasing our product. We hope you are satisfied with the look and performance. If you have any questions, please feel free to call us first before going to the internet. Take your time and it will be a smooth install.

Please review complete instructions prior to installing.

We find it easiest to install the kit as a complete assembly; however, it can be done one piece at a time. Here is a walk through:

Step#	
1	Verify you have all of the following parts included in the kit: (1) JLT Plastic Intake Pipe with PCV & IAT grommet, (1) 4"-3.5" 90° Rubber Elbow, (1) 4.5"x9" Air Filter, (1) JLT Heat Shield, (1) 64 Clamp, (1) 56 Clamp, (1) PCV hose and (1) 10mm nut
2	Gather all of the following tools needed for the installation: 5/16 Nut Driver, 10mm Socket and Ratchet
3	Remove the stock intake from the throttle body to the airbox. There is only one bolt on the airbox and the clamp at the throttle body. 
4	Install JLT Heat Shield, by sitting down on frame rail, clipping onto radiator support and using the supplied nut attached to the apron. 

5	<p>Remove IAT sensor from stock tube and insert into grommet in JLT tube closest to the filter end. Use a screwdriver to pry it out, it will be tight, so use caution.</p> 
6	<p>Loosely install rubber elbow and clamps on JLT tube, insert tube into heat shield and attach to the throttle body.</p>
7	<p>Use supplied PCV hose and make connection between drivers valve cover and JLT tube as well as plug in IAT sensor.</p>
8	<p>Install air filter onto tube, make any adjustments and tighten the clamps. Do not over tighten clamps, they only need tube snug (finger tight).</p> 

Oil Filter: The frequency you should clean your filter will depend on your driving conditions. It is recommended to check your filter at every oil change or 3,000 miles. If there is a build up of dirt as thick as the wire mesh, then it's time to clean your filter. To properly clean your oil filter, we recommend the S&B Precision Cleaning & Oiling Kit (located in the Parts Sold Separately Section of our website, www.JLTtruecoldair.com).

Thanks for the business. If you have any questions, please e-mail info@JLTtruecoldair.com or call 757-335-1940. Our hours are Monday-Friday. 8:00am – 5:00pm Eastern Time.

JLT Performance Lifetime Satisfaction Guarantee. We want you to be a JLT Performance customer for life! Your new JLT Performance product is warranted to be free from defects in materials and workmanship for the life of the *original retail purchaser*, subject to the limitations contained in our warranty found here. www.jlttruecoldair.com/warranty

We guarantee workmanship, tunability and even a pathway to discounted upgrades for substantially improved items.

Return Policy: All returns will be subject to a 10%-25% restocking fee. Air Filters will not be accepted for return unless they are in original plastic sealed bag. Please visit www.JLTtruecoldair.com for complete return policy.

Disclaimer: JLT Performance Inc. makes no warranties whatsoever, expressed or implied, oral or written to any purchasers, except the warranty above. JLT Performance Inc. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by JLT Performance Inc. agree to hold harmless and indemnify JLT Performance Inc. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to JLT Performance Inc. for any claims arising out of use of its products.